



TECHNICAL SPECIFICATIONS

RANGE 70 KM
 LENGTH 3.4 M
 DIAMETER 230 MM
 WEIGHT 215 KG

GUIDANCE GUIDANCE TO COORDINATE, TERMINAL GUIDANCE WITH LASER DESIGNATION

WAR HEAD HIGH EXPLOSIVE, FRAGMENTATION (STEEL BALL)

PLATFORMS MULTI-BARREL ROCKET LAUNCHER WEAPON SYSTEM

ACCURACY ≤ 2 M (CEP)

ANTI-JAMMING CAPABILITY

TARGET TYPE

ARTILLERY AND AIR DEFENSE SYSTEMS, RADAR SITES, COMMAND, CONTROL AND COMMUNICATION SYSTEMS, LOGISTICS FACILITIES, ASSEMBLY AREAS

TRLG-230

The optional use of laser seeker heads on TRG-230 missiles facilitates the neutralisation of point targets while avoiding civilian damage by marking the target from the ground or air. Depending on the weather conditions and the characteristics of the target, assets marked with a laser from a distance can be neutralised by TRG-230 missiles integrated with a Laser Seeker, launched from an artillery battery or unmanned aerial vehicle. After being directed to the target area using inertial guidance methods, the laser seeker directs the missile to the target with pin-point accuracy in the terminal phase.

